Technical data sheet 0° socket, Denmark, single

Item number: 6117201





Socket, single 0°, to Danish standard, with increased touch protection, with screw terminals, 2-pin, 16 A 250 V~, with connection terminals to IEC 60884-1.

For installation in Rapid 45 ducts, device installation ducts, installation columns, underfloor systems and Deskboxes.

PC

Polycarbonate

Master data


Item number	6117201
Туре	SKS-DK0 RW1
Description 1	Socket, Danish version
Description 2	type K
Manufacturer	ОВО
Dimension	45x45x29
Colour	Pure white; RAL 9010
Material	Polycarbonate
Smallest sales unit	12
Unit of quantity	Piece
Weight	3.2 kg
Weight unit	kg/100 pc.

Technical data sheet 0° socket, Denmark, single






Dimensions



45

Width	45 mm
Height	45 mm



Technical data

Cover	Central plate	
Closable	no	
Number of units	1	
Number of poles	2	
Printed label/coding	Without printing	
Version for	Single 0°	
Surface version	Not applicable	
Version for	Danish norm (earthing pin)	
Ejection mechanism	no	
Fastening type	Lock	
Labelling panel	no	
Operating temperature, max.	40 °C	
Operating temperature, min.	-5 °C	
increased touch protection	yes	
Error current protection	no	
For more difficult conditions (according to VDE)	no	
Halogen-free	no	
Hinged cover	no	
Warning light	no	
With on/off switch	no	
With fine-wire fuse	no	
With functional lighting	no	
With orientation lighting	no	
Mounting type	Device installation duct	
Nominal voltage	250 V	
Nominal current	16 A	
Protection rating	Other	
Special power supply	Without special power supply	
Socket angle	0°	
Depth	36 mm	
Transparent	no	
Rotated central insert	no	

Technical data sheet

0° socket, Denmark, single

OBO BETTERMANN

Item number: 6117201

Technical data		
	Surge protection	no